GZNV / INTERNAL GAS BURNER TESTING

Internally valved manual sealing connection tool for Natural Gas or Propane Burner Testing.

CONNECTS TO:



- Lockable collar to keep sealing pressure consistent and internally valved to prevent gas flow once disconnected
- Adjustable ring to accommodate the widest sealing range in the industry
- Internal shut-off valve to stop the flow of gas when handle is in the disconnected position
- 4 Non-sparking aluminum and brass components



SPECIFICATIONS

Pressure Rating	Operating Temperatures	Materials of Construction				
Vacuum to 5 psi (0.345 bar)	0°F to +200°F (-17°C to +93°C)	Anodized Aluminum, Brass, Molded Nylon Handle				
Term	ination Port	Seal Material*				
1/4, 1/2 NPT		Main: Urethane Internal: Buna-N				

^{*} Additional seal material types available, consult factory.

ACTUATION METHOD

Lever Handle: Two way actuation handle is simple and ergonomic for production applications

ICON™ TECHNOLOGY

Consult Factory

ACCESSORIES

Visit fastestinc.com

GZNV / INTERNAL GAS BURNER TESTING



Ordering Information					Dimensions					
Connects To	Part Number	Replacement Seals Bulk Pack (5)	Rebuild Kit	Replacement Shaft	А	В	С	D	M	Т
GZNV W	ith 2 in. (51 mm) Exter	nded Shaft								
3/8 NPT	GZNV0620410200	GZNVB062	GZNVR062	5ZNV27F380200	9.30 (236.2) 9.65 (245.1)	1.88 (47.8)	4.96 (119.1)	1.06 (26.9)		1/4 NPT
1/2 NPT	GZNV0820410200	GZNVB082	GZNVR082	5ZNV275BR0200						
3/4 NPT	GZNV1220810200	GZNVB122	GZNVR122	5ZNV375BR0200		2.44 (61.9)	5.21 (132.3)			1/2 NPT
GZNV Re	duced Length Shaft									
3/8 NPT	GZNV062041*	GZNVB062	GZNVR062	5ZNV27F38BR	7.30 (185.4) 7.65 (194.3)	1.88 (47.8)	4.96 (119.1)	1.06 (26.9)	0.63 (16.0)	1/4 NPT
1/2 NPT	GZNV082041*	GZNVB082	GZNVR082	5ZNV275BR						
3/4 NPT	GZNV122081*	GZNVB122	GZNVR122	5ZNV275BR		2.44 (61.9)	5.21 (132.3)	1.38 (35.1)		1/2 NPT

Dimensions: inch (mm)

*Consult Factory for availability.

GasMate™ GZNV Family Flow Capacity





